



ImageRUNNER
ADVANCE

C2230 / C2225 / C2220 / C2220L

Canon

Delighting You Always



ADVANCED MADE SIMPLE FOR YOU



Business **can** be simple

MAKE IT ADVANCE.

Witness the significant improvement in your business communication capabilities. Move your business forward with the new imageRUNNER ADVANCE C2200 series today.

To arrange for a demonstration, simply contact any of our sales staff in the relevant contact overleaf.

SPECIFICATIONS imageRUNNER ADVANCE C2200 Series

Type	Desktop	
Maximum Original Size	A3	
Copy Sizes	Cassette 1	C2230/C2225/C2220: A3, B4, A4, and B5 C2220L: A3, B4, A4, A4R, B5, B5R, A5R, and Custom size (148 x 182mm to 297 x 420mm)
	Cassette 2 *Optional for C2220L	C2230/C2225/C2220: A3, B4, A4, A4R, B5, B5R, A5R, Custom Size (139.7 x 182mm to 304.8 x 457.2mm), and Envelopes
	Stack Bypass	305 x 457mm, 320 x 450mm (SRA3), A3, B4, A4, A4R, B5, B5R, A5, A5R, Custom Size (99 x 139.7mm to 320 x 457.2mm), and Envelopes** (Optional)
Resolution	Reading	600dpi x 600dpi
	Copying	600dpi x 600dpi
	Printing	1200dpi x 1200dpi (text/line only)
Copy/Print Speed	A4	C2220L: 20ppm (B&W/Color)
		C2220: 20ppm (B&W/Color)
		C2225: 25ppm (B&W/Color)
	A3	C2230: 30ppm (B&W/Color)
		C2220L: 15ppm (B&W/Color)
		C2220: 15ppm (B&W/Color)
Magnification	Zoom	25-400%
	Black-and-White	5.9sec
	Full Color	8.9sec
First Copy Time	34 seconds	
Warm-Up Time	34 seconds	
Multiple Copies/Prints	1 to 999 sheets	
Duplexing	Standard automatic stackless	
Paper Weight	Cassette 1	64 to 120gsm
	Cassette 2* (Optional for IR-ADV C2220L)	64 to 163gsm
	Stack Bypass	64 to 220gsm
	Duplex	64 to 120gsm
Paper Capacity	Standard	Cassette 1 (80gsm): IR-ADV C2220L: 250 sheets IR-ADV C2220/C2225/C2230: 520 sheets
		Cassette 2 (80gsm): 550 sheets (Optional for IR-ADV C2220L) Stack Bypass (80gsm): 100 sheets
	Optional	550 sheets x 2 cassettes (80gsm)
	Total maximum capacity	IR-ADV C2220L: 2,000 sheets IR-ADV C2220/C2225/C2230: 2,270 sheets
CPU	1.67GHz	
Memory	Standard: 2GB RAM	
Hard Disk Drive	Standard 160GB for IR-ADV C2230/C2225/C2220 Optional for IR-ADV C2220L	
Interface	Ethernet (1000Base-T/100Base-TX/10Base-T)	
Power Supply	220-240V AC, 50/60Hz	
Power Consumption	1.5KW max	
Toner (Estimated Yield @ 5% coverage)	23,000 (B&W); 19,000 (Cyan, Magenta and Yellow)	
Drum Yield	IR-ADV C2220/C2220L	43,000 (B&W); 36,000 (Cyan, Magenta and Yellow)
	IR-ADV C2230/C2225	53,000 (B&W); 44,000 (Cyan, Magenta and Yellow)
Dimensions (W x D x H)	Main Unit Only:	IR-ADV C2230/C2225/C2220 - 565mm x 680mm x 791mm IR-ADV C2220L - 565mm x 650mm x 791mm
	Weight	Main Unit Only: IR-ADV C2230/C2225/C2220 - Approximately 79kg IR-ADV C2220L - Approximately 75kg With DADF: IR-ADV C2230/C2225/C2220 - Approximately 86.9kg IR-ADV C2220L - Approximately 82.9kg
Print Specification		
PDL	UFR II (Standard), PCL 5c/6 (Optional), Adobe PostScript 3 (Optional)	
Resolution	1200dpi x 1200dpi (Text/Line only), 600dpi x 600dpi	
Memory	2GB (Uses Main Unit RAM)	
Hard Disk	Standard 160GB for IR-ADV C2230/C2225/C2220 Optional for IR-ADV C2220L	
CPU	Canon Custom Processor, 1.67GHz (Uses Main Unit CPU)	
PS Fonts	Roman 136	
PCL Fonts	Roman 93, Bitmap10, OCR2	
Supported OS	PCL	Windows XP/Server2003/Vista/Server2008/Windows7/Server 2008 R2/Windows 8
	Adobe PostScript 3	Windows XP/Server2003/Vista/Server2008/Windows7/Server 2008 R2/Windows 8, Mac OS X (10.4.9 or later)
UFR II	Windows XP/Server2003/Vista/Server2008/Windows7/Server 2008 R2/Windows 8, Mac OS X (10.4.9 or later)	
Mac-PPD	Mac OS 9.1 or later, Mac OS X (10.2.8 or later)	
Interface	Ethernet (1000Base-T/100Base-TX/10Base-T) Wireless LAN (IEEE802.11b/g, Optional), USB2.0	
Network Protocol	TCP/IP (LPD/Port9100/WSD/IPP/PPS/SMB/FTP), IPv6, IPX/SPX (NDS, Bindery), AppleTalk	
Pull Scan	Network TWAIN Driver	

Send Specification (Optional for IR-ADV C2220L)		
Scan Resolution	100dpi, 150dpi, 200 x 100dpi, 200dpi, 200 x 400dpi, 300dpi, 400dpi, 600dpi	
Destinations	E-Mail/Internet FAX (SMTP), PC (SMB, FTP), WebDAV, Google Docs and Microsoft SharePoint Online with IR-ADV Cloud Connect MEAP application.	
Address Book	LDAP, Local (Max.1800)	
File Format	TIFF, JPEG, PDF, XPS, High compression PDF/XPS, PDF/A-1b, Optimize PDF for Web, OOXML (.LPPTX only) (*To use Optimize PDF for Web, HDD installation is required for IR-ADV C2220L)	
Optional Accessories		
Universal Send Advanced Feature Set-D1		
File Format	Outline PDF (Trace & Smooth), Searchable PDF/XPS, Reader Extensions PDF, OOXML (.LPPTX only)	
Universal Send Security Feature Set-D1		
File Format	Encrypted PDF, Device Signature PDF/XPS	
Duplex Automatic Document Feeder-A1		
Paper Size	A3, B4, A4, A4R, A5, A5R, B5, B5R, or B6	
Paper Weight	1-sided scanning: 42 to 128gsm 2-sided scanning: 50 to 128gsm	
Max. Number of Originals	50 sheets (80gsm)	
Copying:	1-sided scanning - 30 sheets/minute (A4 in B&W/Color at 600dpi)	
Document Scanning Speed (Max.)	Scanning: 1-sided scanning - 51 sheets/minute (A4 in B&W/Color at 300dpi)	
Dimensions (W x D x H)	565mm x 540mm x 135mm	
Weight	Approx. 7.9kg	
Cassette Unit-X1 (Only for IR-ADV C2220L)		
Paper Size	A3, A4, A4R, A5R Custom Size 139.7 x 182mm to 304.8 x 457.2mm	
Paper Weight	64 to 163gsm	
Paper Capacity	550 sheets (80gsm) x 1 cassette	
Cassette Feeding Unit-A1		
Paper Size	A3, B4, A4, A4R, B5, B5R, A5R Custom Size 139.7 x 182mm to 304.8 x 457.2mm	
Paper Weight	64 to 163gsm	
Paper Capacity	550 sheets (80gsm) x 2 cassettes	
Dimensions (W x D x H)	565mm x 650mm x 248mm	
Weight	Approx. 27.5kg	
Inner Finisher F1		
Number of Trays	One stack tray (Optional 2 nd Tray)	
Tray Capacity	A4, A5, A5R	A4-A5R: 750 sheets
	A3, A4R	A3, A4R: 500 sheets
Staple Position	Corner, Double	
Staple Capacity	A4: 50 sheets A3: 30 sheets	
Dimensions (W x D x H)	590mm x 550mm x 260mm	
Weight Approx.	Approx. 14.0kg (when the optional Inner Finisher Additional Tray-F1 is attached)	
Other Optional Accessories		
Platen Cover Type S, Copy Tray Unit-1, Utility Tray-A2, Inner 2 way Tray-F1, 3 Way Unit-C1, Inner Finisher Additional Tray-A1, Buffer Pass Unit-K1, Staple Finisher-M1, Booklet Finisher-M1, Envelope Feeder Attachment-D1, Serial Interface Kit-K1, Copy Control Interface Kit-A1, Copy Card Reader Attachment-B3, Copy Card Reader-F1, FL Cassette-AM1, FL Cassette-AN1, Stamp Ink Cartridge-C1, Stamp Unit-B1, Staple Cartridge-D2, Staple Cartridge-D3, Staple Cartridge-J1, Cassette Heater Unit-37, Reader Heater-J1 200V, PCL Printer Kit-AT1, PS Printer Kit-AT1, Barcode Printing Kit- D1, Direct Print Kit (for PDF)-H1, Direct Print Kit (for XPS)-H1, Canon Color Universal Send Kit-R1, Super G3 Fax Board-AH2, Super G3 2 nd Line Fax Board-AH1, Remote Fax Kit-A1, Web Access Software-H1, Multimedia Reader/Writer-A2, USB Device Port-E2, Secure Watermark-B1, Universal Send Digital User Signature Kit-C1, Removable HDD Kit-AE1, IR-ADV Security Kit-D1, HDD Encryption Kit-C3, 2.5inch/80GB HDD-E2, Encrypted Printing Software-D1, Document Scan Lock Kit-B1, Access Management System Kit-B1, ADF Access Handle-A1, Remote Operators Software Kit-B1, Voice Guidance-F2, Voice Operation Kit-C2		
This brochure and the specifications of the product have been developed prior to the date of product launch. These specifications are subject to change without notice. Therefore no representations or warranties, either express or implied, are made of the fitness of this product for a particular purpose. In no circumstances shall the information in this brochure be considered part of our terms and conditions of sale. You are advised to check the prevailing specification immediately prior to purchase. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.		

