

# Canon imageRUNNER™ 2270/2870/3570/4570



## Smart Design, Compact Space Saving Body

With a newly designed paper feed unit, a compact duplex unit, and a stack bypass tray that folds flatly, the space needed to setup the machine has been reduced. In addition, paper jams can be accessed from the right side of the machine and thus allows corner setup of the machine.

## Unparalleled Multifunctionality

Equipped with a 300MHz processor, 256MB RAM and a 20GB hard disk as standard. Large memory capabilities enable simultaneous processing of multiple tasks or full concurrency.

## Large Format Color Touch Panel even on Monochrome Machine

A large 7.8 color LCD touch panel with easy-to-use menu layout enables first time users to intuitively master the functions of the imageRUNNER 2270/2870/3570/4570.

## Control and Manage Resources Anywhere

The imageRUNNER 2270/2870/3570/4570 offers all tools that aid administrators with installing, accessing, managing and protecting vast fleets of network-connected devices.

- Offers another option that increases user's protection against information theft- the imageRUNNER Security Kit.
- Through Department ID Management, you can register a Department ID and password for each department. Up to 1,000 departments can be registered for complete control of copy, scan and print totals.



# Canon

## imageRUNNER™

### 2270/2870/3570/4570



#### imageRUNNER 2270/2870/3570/4570 Specifications

##### Main Unit

Type:	Desktop	
First-Copy Time:	IR 2270/2870	4.9 seconds
	iR 3570/4570	3.9 seconds
Warm-Up Time:	IR 2270/2870	30 seconds max after powering on (20 °C)
	IR 3570/4570	40 seconds max after powering on (20 °C) 10 seconds from Sleep Mode (approximate)
Copy Speed:	22/28/35/45ppm (A4)	
Acceptable Originals:	Sheet, book, three dimensional objects (up to 2kg)	
Max. Original Size:	A3	
Max. Copy Size:	A3	
Min. Copy Size:	A5	
Max. Mail Boxes Supported:	100	
Max. Copy Reservation:	5 jobs	
Copy/Scan Resolution:	600 dpi x 600 dpi	
Print Resolution:	2400 dpi x 600 dpi Interpolated	
Automatic Exposure:	AE or Manual (Text, Photo, or Text and Photo)	
Halftones:	256 Gradations	
Paper Feed:	Automatic Dual-Sided Document Feeder	
Magnification:	25% to 400% (in 1% increment)	
Paper Sources		
Standard:	Paper Cassettes	550 sheets x 2
	Stack Bypass	50 sheets
Optional:	Dual Paper Cassettes	550 sheets
	Paper Deck	2,500 sheets
		(Total: 4,750 sheets)
Multiple Copies:	1 to 999	
Paper Weights:	Cassette	64 to 128g/m <sup>2</sup>
	Stack Bypass	64 to 128g/m <sup>2</sup>
Dimensions (W x D x H):	565 x 700 x 761.4mm	
Weight:	61.6 kg	
Power Requirements:	230V/6A/50Hz	
Power Consumption:	1.35 kW maximum	

##### Accessories

##### Duplexing Automatic Document Feeder-N1

Acceptable Originals:	A5 to A3
Capacity:	50 sheets (80g/m <sup>2</sup> )
Max. Paper Weights:	42 to 128 gsm (A4)

##### Cassette Feeding Unit-Y2

Paper Capacity:	Dual Paper Cassettes	550 x 2 sheets
Paper Size:	A5R to A3	
Paper Weights:		64 to 128 g/m <sup>2</sup>

##### Finisher-S1

Tray Type:	Descending Stack Tray
Paper Weight:	64 to 128 g/m <sup>2</sup>
Capacity Per Tray:	No collate, Collate, Group Mode 1,000 sheets (A4, B5, A5R)
	Staple Mode 1,000 sheets/30 sets (A4, B5)
Max. Stapling Capacity:	A4, B5: 50 sheets (64 g/m <sup>2</sup> to 80 g/m <sup>2</sup> )

##### Finisher-Q3

Number of Trays:	Two Trays (upgradable to 3)
Paper Weight:	64 to 128 g/m <sup>2</sup>
Capacity Per Tray:	No collate, Collate, Group Mode 1,000 sheets (A4, B5, A5R)
	Staple Mode 1,000 sheets/30 sets (A4, B5)
Max. Stapling Capacity:	A4, B5: 50 sheets (64 g/m <sup>2</sup> to 80 g/m <sup>2</sup> )

##### Saddle Finisher-Q4

Number of Trays:	Three Trays, including Saddle-stitch
Paper Weight:	64 to 128 g/m <sup>2</sup>
Capacity Per Tray:	No collate, Collate, Group Mode 1,000 sheets (A4, B5, A5R)
	Staple Mode 1,000 sheets/30 sets (A4, B5)
	Saddle Stitch Mode 1 to 5 sheets/25 sets

##### Super G3 Fax Board-Q1

Applicable Line:	Public Switched Telephone Network (PSTN)
Connection Lines:	One (J1)
Transmission Time*:	ECM-MMR Approx. 3 Seconds per page (33,600 bps)
Compression System:	MMR, MR, MH, JBIG
Sending Sizes:	A5 to A3

##### Multi-PDL Printer Kit-E1

Processor:	Canon Custom Processor 300MHz
RAM:	512MB (Std/Max) Shared
Hard Disk:	20GB Shared
PDL Support:	PCL6, PCL5e, UFR II, PostScript <sup>®</sup> 3™ Emulation
Interface Connection:	Standard RJ-45 (10/100Base-T)
	USB Full-speed (2.0 Equivalent)

##### Network OS:

Windows, 98/Me/2000/XP/NT, 4.0/Server 2003 (32bit)  
Solaris™ 1.x, 2.5, or later  
Apple<sup>®</sup> System 7.5 or higher  
Novell<sup>®</sup> Netware v3.2, 4.1, 4.11, 4.2, 5, 5.1, 6.0



**SASTRONIC** 实力有限公司  
**SDN BHD**  
(427626 D)

44, Jalan S2/C2, Green Technology Park, S'ban2, 70300 Seremban, NSDK.

**SALES ENQUIRIES: 销售热线:**

Tel: **06-601 4544** Fax: **06-601 3976**

H/P: **012-6112206, 012-6083772**

Website: **www.sastronic.com.my**

*Copier \* Fax \* Office Equipment \* Paper Distributor*