

THE DOCUMENT COMPANY  
**FUJI XEROX**

**DocuCentre-II**  
**C4300/C3300/C2200**  
Digital Colour Multifunction Device



Advanced features  
for industry-leading  
performance

With security for greater peace of mind



CONFIGURATIONS		DocuCentre-II C4300	DocuCentre-II C3300	DocuCentre-II C2200
Output Speed*1*2	B&W	45 ppm	35 ppm	26 ppm
	Colour	35 ppm	31 ppm	26 ppm
<b>PAPER HANDLING</b>				
Duplex Automatic Document Feeder	Capacity	75 sheets*3		
	Scanning Speed	45 dpm (B&W); 35 dpm (Colour)	35 dpm (B&W); 31 dpm (Colour)	26 dpm (B&W); 26 dpm (Colour)
Paper Trays Capacity*3*4		Tray 1 to 4: 500 sheets each Bypass Tray: 90 sheets		
Paper Weight		Tray 1 to 4: 60 gsm to 169 gsm Bypass Tray: 55 gsm to 220 gsm		
Finishing Options (Optional)	B Finisher	Stapling		
	C Finisher	Stapling and Hole Punching		
	C Finisher with Booklet Maker	Stapling, Hole Punching and Saddle Stitch Booklet Making		
<b>PRINT</b>				
Processor		PowerPC G2 667 MHz		
Memory		Standard: 256MB		
		Maximum: 1G		
		HDD: 40GB		
Resolution		Up to 1,200 x 1,200 dpi*5		
PDL	Standard	PCL6, PCL5, HPGL/HPGL-2, TIFF, PDF KS/KSMM (Korean version only) ESCP/K (Traditional Chinese version only)		
	Optional	Adobe PostScript Level 3		
Operating System Support	Standard	Win95/98/ME, 2000/XP, NT4.0, WinServer2003, MetaFrame1.8/XP		
	Postscript (Optional)	Win95/9/ME, 2000/XP, NT4.0, WinServer2003, MacOS [7.5.3 - 9.2.2]. MacOSX [10.1.5/10.2.x/10.3.3 - 10.3.9]		
Connectivity	Standard	100Base-TX/10Base-T		
	Optional	Parallel Port (IEEE1284-B), USB2.0		
Protocol		TCP/IP, SMB, IPP, Port9100, EtherTalk*6		
<b>COPY</b>				
First Copy Out Time		4.8 sec (B&W); 7.2 sec (Colour)	5.7 sec (B&W); 7.5 sec (Colour)	5.7 sec (B&W); 7.5 sec (Colour)
Resolution		600 x 600 dpi		
Reduction / Enlargement		25% - 400%		
<b>SCAN (Optional)</b>				
Speed*2*7		50 dpm (B&W); 45 dpm (Colour)		
Resolution		Up to 600 x 600 dpi		
Maximum Scan Area		A3		
Output Format	B&W	TIFF (MH, MMR), PDF, XDW		
	Colour / Grey Scale	TIFF (MH, MMR), JPEG, PDF, XDW		
Scan Destinations		FTP, SMB, E-mail, Mailbox		
<b>FAX (Optional)</b>				
Transmission Speed		3 seconds or less		
Compression System		MH, MR, MMR, JBIG		
Resolution		Up to 600 x 600 dpi		
No. of Fax Line	Standard	1 Line		
	Optional	Max. 2 Lines can be added (total 3 lines)		
<b>GENERAL</b>				
Power Source		A220-240±10%/110V±10%, 10/15A for both 50/60Hz		
Power Consumption		Max Power Consumption: 1.5KVA or less		
		Low Power Mode: 90W		
		Sleep Mode: 10W		
		Standby Mode: 230W		
Warm-Up Time		45 seconds or less		
Dimensions*8 and Weight*9		666mm (W) x 789mm (D) x 1,141mm (H); 166kg*10		
Space Requirements*11		967mm (W) x 789mm (D) (without Finisher)		
		1.504mm (W) x 789mm (D) (with B Finisher)		
		1.797mm (W) x 813mm (D) (with C Finisher)		
		1.856mm (W) x 813mm (D) (with C Finisher with Booklet Maker)		

\*1 The speed may be reduced due to image quality adjustment

\*2 A4-size paper LEF

\*3 80 gsm paper

\*4 For Tandem Tray Model: Tray 1&2: 500 sheets each; Tray 3: 875 sheets; Tray 4: 1,145 sheets; Bypass Tray: 90 sheets

\*5 In Super-Fine mode with continuous speed of: C4300 - 22 cpm; C3300 - 22 cpm; C2200 - 16 cpm for B&W or Colour with A4

\*6 The Optional PostScript3 Kit is required

\*7 200 dpi

\*8 Excluding optional accessories

\*9 Excluding paper, optional accessories, and consumables

\*10 For Tandem Tray Model: 175 kg

\*11 When the bypass tray is extended completely  
+ Optional

