

you can  
**Canon**

**iR7105**  
Black and White  
Light Production

## High-speed production with outstanding finishing



Ultimate mid range  
solution for demanding  
production environments

There are no limits to your production capabilities thanks to Canon's iR7105 flagship Light Production print engine.

Designed to effortlessly cope with your toughest schedules, it prints at a super-quick 105 pages per minute and is configurable with a range of finishing options unmatched at this end of the market.

# Specifications iR7105

<b>PRINTING ENGINE</b> Type Print Speed Printing Resolution Image Server Network Interface Connections Dimensions (HxWxD) Weight Power Requirements Power Consumption	Digital Multifunction Imaging System 105ppm (A4), 53ppm (A3) 1200 dpi x 1200 dpi* Standard 1GB RAM / 40GB Hard Disk Drive 10/100 Base-TX (RJ-45) 1474mm x 1216mm x 783mm 270kg 230 V, 13 A, 50 Hz 2.5 kW (Max.) or less
<b>PAPER SUPPLY</b> Max. Original Size Paper Weight Standard Paper Capacity Drawers 1 & 2 Drawers 3 & 4 Bypass Tray Max. Paper Capacity	Paper Drawers A3 (Bypass Tray; 297 x 432mm - Free Size) 64 – 200gsm (Drawers, Bypass Tray and Paper Decks) 4150 Sheets (80gsm) 1,500 sheets each 550 sheets each 50 sheets 7650 sheets (80gsm) with optional Paper Deck W1 or X1
<b>PAPER DECK – W1 (OPTIONAL)</b> Paper Size Paper Capacity Dimensions (HxWxD) Weight	A4 3500 sheets 570mm x 323mm x 583mm 41Kg
<b>PAPER DECK – X1 (OPTIONAL)</b> Paper Size Paper Capacity Dimensions (HxWxD) Weight	A4, A3 3500 sheets 575mm x 593mm x 621mm 46Kg
<b>DOCUMENT INSERTER – C1 (OPTIONAL)</b> Paper Size Paper Weight Paper Capacity Dimensions (HxWxD) Weight	Upper Tray: A5, A4 Lower Tray: A5, A4, A3 64 – 300gsm 200 sheets x 2 Trays 213mm x 625mm x 667mm 17Kg
<b>STANDARD FINISHER – V1</b> Stacking Capacity Stapling Stapling Capacity Dimensions (HxWxD) Weight	Upper Tray: 3000 Sheets (A4) Lower Tray: 2000 Sheets (Total 5000 80gsm Sheets) Any corner or double stapling 100 sheets (A4), 50 sheets (A3) 1180mm x 800mm x 792mm 126Kg

<b>SADDLE FINISHER – V2</b> Stacking Capacity Stapling Stapling Capacity Saddle Stitch Paper size Saddle Stitch Capacity Dimensions (HxWxD) Weight	Upper Tray: 3000 Sheets Lower Tray: 2000 Sheets (Total 5000 80gsm Sheets) (stacking capacity reduced to 3000 sheets when Trimmer – B1 is installed) Any corner or double stapling 100 sheets (A4), 50 sheets (A3) A4R, A3 20 Sheets (80 pages) 1180mm x 800mm x 792mm 178Kg
<b>HIGH CAPACITY STACKER – A1 (OPTIONAL)</b> Paper Capacity Tray Capacities Paper Sizes for Stack Tray Paper Weights Stacking Modes Power Source Dimensions (H x W x D) Weight	6,000 Sheets Total 1,000 sheet Top Output Tray 5,000 sheet Stack Tray A4, A3 64 to 200 gsm Straight, Offset non-stapled 220V, 50Hz 1290 mm x 860 mm x 765 mm Approximately 200 Kg.
<b>PERFECT BINDER – A1 (OPTIONAL)</b> Bookbinding Method Bookbinding Thickness Book Size Margin Trimming Insertion Unit Capacity Cover Size Paper Weights Power Source Dimensions (H x W x D) Weight	Hot Glue Spine with Wraparound Cover Approx. 10 to 200 sheets (1mm to 20mm) A4 (Maximum Before Trimming) Integral trimming device – 3 Sides or no trimming Upper Tray: 200 sheets (A4 80 gsm) Lower Tray: 200 sheets (A4 80 gsm) A3+ 64 – 163 gsm (Insertion sheets) 64 – 300 gsm (Cover sheets) 220V, 50Hz 1360 mm x 920 mm x 783 mm Approximately 324 kg
<b>STANDARD PUNCH UNIT – U1/W1 (OPTIONAL)</b> Paper Sizes Punch Paper Weight Punch Patterns Dimensions (H x W x D) Weight	A4, A3 64 – 200 gsm 2 Hole (Unit – U1) or 4 Hole (Unit – W1) 978 mm x 305 mm x 723 mm Approximately 70 Kg
<b>PROFESSIONAL PUNCHER – A1 (OPTIONAL)</b> Punch Paper Size Punch Paper Weight Punch Patterns (Optional) Dimensions (H x W x D) Weight	A4 75 to 200 gsm Standard 2 and 4 Hole Plastic Comb (21 hole) Twin Loop (34 hole) Twin Loop (23 hole) Color Coil (47 hole) Velo Bind (12 hole) 978 mm x 305 mm x 723 mm Approximately 70 Kg

<b>PAPER FOLDING UNIT – D1</b> Fold Type Paper Size Paper Weight Power Source Dimensions (H x W x D) Weight	Z Fold A3 64 – 80gsm From Finisher Module 1040mm x 179mm x 786mm 44Kg
<b>BOOKLET TRIMMER – B1</b> Trim Thickness Output Tray Capacity Paper Sizes Paper Weights Power Source Dimensions (H x W x D) Weight	40 sheets (80 gsm) Conveyor Belt with 30 Booklets A4R, A3 64 – 200gsm (insertion sheets) 64 – 300gsm (cover sheets) From Finisher Module 1040 mm x 1575 mm x 770 mm Approximately 152 Kg.
*Except PCL – this will be available post launch Perfect Binder - A1 available post launch Perfect Binder - A1 can not be installed with Professional Puncher - A1 Professional Puncher - A1 can not be installed with Perfect Binder - A1 or Standard Puncher - U1/W1 Booklet Trimmer - B1 requires Saddle Finisher - V2 Canon recommends you use Canon Media for the best results. Please check media (paper) compatibility list to see which variety of paper/media is recommended. Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice.™ and ®: All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries. Perfect Binder - A1 can not be installed with Professional Puncher - A1. Professional Puncher - A1 can not be installed with Perfect Binder - A1 or standard Puncher - U1/W1. Booklet Trimmer - B1 requires Saddle Finisher - V2.	
<b>NETWORK MULTI-PDL</b> <b>PRINTER KIT – H1</b> Processor Memory Hard Drive PDL Printing Support Interface Connection Protocols Supported Supported Operating Systems	Canon Dual Custom Processors 400MHz (Main), 666 MHz (Sub) 1 GB (From main unit) 40 GB (From main unit) PCL5e, PCL 6, PostScript 3 Emulation, UFR II PDF, TIFF, JPEG 10/100 Ethernet, USB High-Speed (2.0) IPX/SPX, TCP/IP, SMB, AppleTalk Supported Operating Systems Windows 98/ME/2000/XP/Server 2003/NT 4.0 Novell NetWare v.3.2 or later, Solaris 1.1x, 2.5x or later, Mac OS 8.0 or later
<b>NETWORK MULTI-PDL</b> <b>PRINTER UNIT – S1</b> Processor Memory Hard Drive PDL Printing Support Interface Connection Protocols Supported Supported Operating Systems	Intel CeleronD 2.8GHz 256 MB 80 GB PCL 5e, PCL 6; Adobe Postscript 3 PDF, TIFF, JPEG 10/100/1000 Ethernet IPX/SPX, TCP/IP, SMB, AppleTalk Supported Operating Systems Windows 98/ME/2000/XP/Server 2003/NT 4.0 Novell Netware v. 4.2, 5.1 or 6 Mac OS 9.X, Mac OS X and Unix (LPR Printing)



44 Jalan S2/C2, Green Technology Park, S'ban2, 70300 Seremban, NSDK.

**SALES ENQUIRIES: 销售热线:**

Tel: 06-601 4544 Fax: 06-601 3976

H/P: 012-6112206, 012-6083772

Website: [www.sastronic.com.my](http://www.sastronic.com.my)

Copier \* Fax \* Office Equipment \* Paper Distributor

