

imageRUNNER ADVANCE 6055/i 6065/i 6075/i

The next level in
office productivity.

you can

Move your business forward with our most advanced series of multifunctional black and white office devices. Boosting office productivity and transforming document workflows, they offer advanced security capabilities and outstanding environmental credentials.



55 – 75

PPM PPM
MONO

PERSONAL USER
INTERFACE

UP TO 7,700
SHEET PAPER
CAPACITY

EXCEPTIONAL
SCANNING
CAPABILITY

ADVANCED
FINISHING
CAPABILITIES

MODULAR
DESIGN

Productivity

- Highly intuitive 8.4" colour touch-screen user interface
- Create "one-touch" buttons to execute common tasks
- High speed duplex scanning up to 200 ipm
- Seamless scanning into business applications
- Integrated software options provide powerful end-to-end workflow solutions

Environmental

- Excellent energy efficiency: as little as 1.5 watts power consumption in sleep mode
- Energy Star certified
- Incorporates recycled materials and Bio plastics

Security

- Advanced security features spanning document confidentiality, integrity and availability
 - Seamless integration with Canon uniFLOW OM solution
 - Compliance with Common Criteria at EAL3 level*
- *Requires optional HDD Data Encryption & Mirroring Kit

Finishing & Quality

- Advanced finishing (booklet & staple finishing, C & Z folding, inserting, hole punching)
- Superb 1200 dpi print quality
- Optional Genuine Adobe PostScript & Fiery based RIP



imageRUNNER
ADVANCE

Canon

Specifications: imageRUNNER ADVANCE 6055/i 6065/i 6075/i

BASIC SPECIFICATIONS	
Type	Console
Maximum Original Size	A3
Copy Sizes	Cassette 1, 2: A4 Cassette 3, 4: A3 to A5R, Free size (139.7 x 182 to 297 x 487.7) Stack Bypass: A3 to A5R, Free size (100 x 148 to 297 x 487.7)
Resolution	Reading: 600dpi x 600dpi, Copying: 1200dpi x 1200dpi Printing: 1200dpi x 1200dpi, 256 Gradients
Copy/Print Speed	A4: 55 ppm (iR-ADV 6055/i), 65 ppm (iR-ADV 6065/i), 75 ppm (iR-ADV 6075/i), A3: 32 ppm (iR-ADV 6055/i), 32 ppm (iR-ADV 6065/i), 37 ppm (iR-ADV 6075/i)
Enlargement/ Reduction	Zoom: 25 - 400%
First copy time	Fixed: Zoom Ratio 25%, 50%, 70%, 100%, 141%, 200%, 400% 3.3 seconds (iR-ADV 6055/i, iR-ADV 6065/i), 3.1 seconds (iR-ADV 6075/i)
Warm-Up Time	38 seconds or less
Multiple Copies/Prints	1 to 9999 sheets
Duplexing	Standard Automatic
Paper weight	Cassettes: 52 to 220gsm, Stack Bypass: 52 to 256gsm Duplex: 52 to 220gsm
Paper Capacity	Standard: 1,500 sheets x 2 Cassettes (3,000 sheets), 550 sheets x 2 Cassettes (1,100 sheets) Stack Bypass: 100 sheets, Optional: Side Paper Deck: 3,500 sheets, Max paper capacity: 7,700 sheets
Processor speed	1.2GHz
Memory	1.5GB (optional 512MB available)
Hard Disk Drive	Standard 80GB, Expandable up to 250GB
Display	8.4" TFT SVGA Colour Touchscreen, Optional 10.4" TFT SVGA Colour Touchscreen
Interface	Ethernet (1000Base-T/100Base-TX/10Base-T), Wireless LAN (IEEE802.11b/g (Optional), USB2.0
Network Protocols	TCP/IP (LPD/ Port 9100/ IPP/ SMB/ FTP), IPX/ SPX (NDS, Bindery), AppleTalk, <i>IPv4/IPv6 support</i> 220-240V, 10A 50/60Hz
Power Supply	2.2 kW Max.
Power Consumption	645mm x 770mm x 1220mm
Dimensions (W x D x H)	942mm x 1289mm
Installation space (W x D)	Approx. 235kg
Weight	
PRINT SPECIFICATIONS	
Page Description Language(s)	UFRIL (Standard on all models), PCL5e/6: (Standard for i models, Optional for non i-models with Canon PCL Printer Kit-A1), Adobe PostScript 3 (Optional on all models with Canon PS Printer Kit-A1)
Resolution	1200dpi x 1200dpi, 600dpi x 600dpi
Fonts	PCL fonts: 93 Roman, 10 Bitmap, 2 OCR, PS fonts: 136 Roman
Supported Operating Systems	UFRIL: Windows 2000/ XP/ Server 2003/ Vista/ Server 2008/ Windows 7/ Server 2008 R2, MAC OS X (10.4.9 or later) PCL: Windows 2000/ XP/ Server 2003/ Vista/ Server 2008 / Windows 7/ Server 2008 R2 PS: Windows 2000/ XP/ Server 2003/ Vista/ Server 2008/ Windows 7/ Server 2008 R2, MAC OS X (10.4.9 or later) MAC-PPD: MAC OS 9.1 or later, MAC OS X (10.2.8 or later)
FIERY BASED PRINTING	
Name	imagePASS-U1 (Optional)
Page Description Language(s)	Adobe PostScript 3, PCL6 / PCL5e
Resolution	1200dpi x 1200dpi, 600dpi x 600dpi,
Memory	2GB
Hard Disk	80GB
CPU	Intel Core Duo T2500, 2.0GHz
Fonts	PS: 136 Adobe PS Fonts, PCL: 113 PCL Fonts
Supported Operating Systems	Windows 2000 (Printer driver only)/ XP(SP3)/Server 2003 (SP2)/ Server 2008(SP2)/ Vista(SP2)/ Vista SP1/ Windows 7 (Printer driver only), MAC OS (10.4 or later)
Interface	Ethernet (1000Base-T/100Base-TX/10Base-T), USB, D-sub 15-pin connector
Network Protocol	TCP/IP (LPD/ Port 9100/ IPP/ SMB/ FTP), AT/ DDP(AppleTalk)
SCAN SPECIFICATIONS	
Optional/Standard	Requires optional Duplex Colour Image Reader Unit-C1
Scan Speed	Scan (Single side): A4 120 ipm 300dpi (BW), 85 ipm 300dpi (Colour), Scan (Double side): A4 200 ipm 300dpi (BW), 100 ipm 300dpi (Colour)
Scan Resolution	100dpi, 150dpi, 200 x 100dpi, 200dpi, 200 x 400dpi, 300dpi, 400dpi, 600dpi (600dpi colour scanning requires optional Memory Type B - 512MB)
Pull Scan	Via Network TWAIN Driver (75 to 600 dpi Black & White and Colour) Pull Scan Supported OS: Windows 2000/ Windows XP/ Windows Server 2003/ Windows Vista/ Windows Server 2008/ Windows 7, (32 bit, 64 bit in compatibility mode)
SEND SPECIFICATIONS	
Optional/Standard	Requires optional Duplex Colour Image Reader Unit-C1
Destinations	E-Mail/ Internet FAX (SMTP), PC (SMB, FTP), WebDAV
Address book	LDAP, Local (Max. 1800)
File Format	TIFF, JPEG, PDF, XPS, High compression PDF/XPS, PDF/A-1b, Optimize PDF for Web
Universal Send Feature Sets:	Universal Send Advanced Feature Set-E1 (option): Outline PDF (Trace & Smooth), Searchable PDF/XPS, Reader Extensions PDF Universal Send Security Feature Set-D1 (option): Encrypted PDF, Device Signature PDF/XPS, Universal Send Digital User Signature Kit-C1 (option): User Signature PDF/XPS

DOCUMENT FEEDER	
Colour Image Reader Name	Duplex Color Image Reader Unit-C1 (Optional)
Paper size	A3, A4, A4R, A5, A5R
Paper weight	Single sided original: 38 to 220 gsm, Double sided original: 64 to 220 gsm
Max. Number of originals	300 sheets (80 gsm)
Scanning speed (max.)	Copy (Single side): A4 120 ipm 600dpi (B&W) Scan (Single side): A4 120 ipm 300dpi (B&W), 85 ipm 300dpi (Colour) Copy (Double side): A4 120 ipm 600dpi (B&W) Scan (Double side): A4 200 ipm 300dpi (B&W), 100 ipm 300dpi (Colour)
Dimensions (WxDxH)	635mm x 605mm x 253mm
Weight	Approx. 39.4kg
PAPER DECK UNIT-A1	
Paper Size	A4
Paper Weight	52 to 220 gsm
Paper Capacity	3,500 sheets (80 gsm)
Dimensions (W x D x H)	323mm x 583mm x 570mm
Weight	Approx. 37kg
PAPER DECK UNIT-D1	
Paper Size	A3, A4, A4R
Paper Weight	52 to 220 gsm
Paper Capacity	3,500 sheets (80 gsm)
Dimensions (W x D x H)	601mm x 621mm x 570mm
Weight: Approx	57 kg
STAPLE FINISHER-E1 BOOKLET FINISHER-E1	
Number of Trays	3
Tray Capacity	Tray A: A4/A5R 250 sheets, A3/A4R 125 sheets, Tray B: A4/A5R 1,300 sheets, A3/A4R 650 sheets, Tray C: A4 2,450 sheets, A5R 1,700 sheets, A3/A4R 650 sheets
Paper Weight	64 to 105 gsm
Staple Position	Corner, Double, Booklet Stitch (Booklet Finisher only)
Staple Capacity	A4: 50 sheets, A3/A4R : 30 Sheets
Booklet Stitch Paper Size	A3, A4R (Booklet Finisher-E1 only)
Booklet Stitch Staple Capacity	16 sheets (64 pages, 64-81gsm) (Booklet Finisher-E1 only)
Dimensions (W x D x H)	Staple Finisher-E1: 748mm x 656mm x 1121mm Booklet Finisher-E1: 748mm x 656mm x 1121mm
Weight	Staple Finisher-E1: Approx. 48kg Booklet Finisher-E1: Approx. 70.5kg
PUNCHER UNIT/S	
(All Puncher Units require either the Booklet Finisher-E1 or Staple Finisher E1)	External 2 Hole Puncher-A1: 2 holes, External 4 Hole Puncher-A1: 4 holes (Swedish), External 2/4 Hole Puncher-A1: 2 holes, 4 holes (French)
DOCUMENT INSERTION/ FOLDING UNIT-H1	
Number of insertion trays	Requires either Booklet Finisher-E1 or Staple Finisher-E1 1 Tray
Paper Size / Paper Weight	A3, A4, A4R / 60 to 256 gsm
Insertion Capacity	100 sheets (80 gsm)
C-Fold Paper Size/ Weight	A4R/ 60 to 105 gsm
Z-Fold Paper Size/ Weight	A3, A4R/ 60 to 105 gsm
Output Capacity	40 Sheets
Dimensions (W x D x H)	662mm x 679mm x 1242mm
Weight	Approx. 76kg
DOCUMENT INSERTION UNIT-L1	
Number of insertion trays	Requires either Booklet Finisher-E1 or Staple Finisher-E1 1 Tray
Insertion Paper Size	A3, A4, A4R
Paper Weight	60 to 256 gsm
Insertion Capacity	100 sheets (80 gsm)
Dimensions (W x D x H)	662mm x 679mm x 1242mm
Weight	Approx. 40kg
ADDITIONAL OPTIONS	
	Printer Cover-B1, Stamp Ink Cartridge-C1, ADF Access Handle-A1 Direct Print Kit (for PDF/XPS)-H1, Barcode Printing Kit-D1, Data Erase Kit-C1, HDD Data Encryption & Mirroring Kit-C2, Encrypted Printing Software-D1, Secure Watermark-B1, Web Access Software-H1, Access Management System Kit-B1, Expansion Bus-F1, Wireless LAN Board-B1, IPsec Board-B2, 2.5inch/80GB HDD-C1, 2.5inch/250GB HDD-D1, Removable HDD Kit-AD1, Document Scan Lock Kit-A1, Seequence compose (For IMAGEPASS-U1), Seequence impose (For IMAGEPASS-U1), Seequence Suite (For IMAGEPASS-U1), REMOVABLE HDD KIT-B4 (For IMAGEPASS-U1), Super G3 FAX Board-AF1, Super G3 2nd Line Fax Board-AF1, Remote Fax Kit-A1, Tab Feeding Attachment Kit-B1, Staple-J1, Staple Cartridge-D3, Shift Tray-A1, Copy Tray-C1, Upright Control Panel-A1, Card Reader-C1, Copy Card Reader Attachment-A2, Utility Tray-A1, Control Panel Sheet-B1, Remote Operator's Software Kit-B1, Voice Guidance Kit-F1, Multimedia Reader/Writer-A1, Serial Interface Kit-K1
Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final are subject to change without notice. ® and ©: All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.	
Canon recommends you use Canon Media for the best results. Please check media (paper) compatibility list to see which variety of paper/media is recommended.	



Canon Inc.
www.canon.com

Canon Europa N.V.
www.canon-europe.com

English-UK Edition 00000
© Canon Europa NV 2010